

DATASHEET ANDRENA 12V7.5Ah

Light-weight, high-performance, safe and reliable lithium power battery, especially developed for motorsports. This battery equals a lead-acid battery of 12 to 20Ah, provided the alternator's maximum current doesn't exceed the battery's maximum charge current of 27A. Designed in a standard rally casing. Suitable for 12V systems and for use in extreme environments.

LIGHTWEIGHT POWER

With a weight of only 1.3kg /3.0lbs, the Andrena 12V7.5Ah power battery saves up to 80% in weight in comparison to traditional lead-acid batteries and is only 1/3 of the size of a conventional battery. This improves not only the performance of your vehicle but also helps to increase the fuel economy.








The power battery offers a high level of power, fast charging and a long, maintenance-free service life. It also has a stable and flat discharge which means you have over 80% of the batteries capacity available and you can leave your vehicle unattended for a much longer period compared to a lead-acid battery.



SAFE AND RELIABLE

Super B batteries are based on lithium iron phosphate technology (LiFePO₄). This is the safest lithium technology available today. On top of that our bespoke casing and electronics further increase safety and durability. Due to its high ingress protection class (IP69) the battery is completely dust tight and waterproof. Therefore the battery can be used in the most extreme environment as well.

PERFORMANCE

- | | | | | | | |
|---|---|---|---|--|---|---|
|  |  |  |  |  |  |  |
| Fast charging | Lightweight | Long and maintenance free lifespan | Compact size | Low self-discharge | High discharge rates | Safest Lithium Iron Phosphate Technology (LFP) |

3-YEAR WARRANTY

Super B's 3-year warranty offers the best peace of mind. It is the benefit of years of continuous engineering improvement and proven experience with all of our batteries in the harshest environments.



ELECTRICAL SPECIFICATIONS

Nominal Capacity	7.5Ah
Energy	96Wh
Nominal Voltage	12.8V
Open Circuit Voltage	13.2V
Self Discharge	<3% per Month
Cycle life	>1000 (at 10C discharge, 100% DoD)
EqPb (Equals lead-acid)	12 to 20Ah

CHARGE & DISCHARGE SPECIFICATIONS

Charge Method	CCCV
Charge Voltage	14.3V - 14.6V
Max Charge Current	27A
End of Discharge Voltage	8V
Discharge Current Continuous	120A
Discharge Pulse Current (1 sec)	375A (50C)

COMPLIANCE SPECIFICATIONS

Certifications	CE, UN 38.3, UL 1642 (Cells)
Shipping Classification	UN 3480

¹Do not charge below 0°C / 32°F

MECHANICAL SPECIFICATIONS

Dimensions (LxWxH)	120 x 82 x 98mm 4.72" x 3.23" x 3.86"
Weight	1.3 kg / 3.0lbs
Case Material	PC - ABS
Ingress Protection	IP69
Cell Type / Chemistry	Cylindrical - LiFePO4

TEMPERATURE SPECIFICATIONS

Charge Temperature	0°C to 55°C ¹ 32°F to 131°F ¹
Discharge Temperature	-30°C to 55°C -22°F to 131°F
Storage Temperature	-40°C to 60°C -40°F to 140°F

GENERAL PRODUCT SPECIFICATIONS

EAN-13	8718531360020
Battery Designation	4IFpR27/66-3